



Compiled/Updated	LL
Approved	CD
Issued Date	20-5-26
Revision	1

# Product Data Sheet - Tiger Tails (LV)

PE Line Guards for covering conductors and power lines for visual warning, mechanical protection and insulation.

### Key Features:

- Unique striped pattern provides class leading visual warning.
- Decades of use, trusted by utility companies worldwide.
- Full compliance with Australian Standards.
- Ideal for use around construction sites to act as a visual warning up to 650v use.
- Also utilised by linesman as insulation and brush contact protection.
- Comes with eyelet in bell housing, which when interconnected, provides a through hole that can accommodate a cable/zip tie for long term installations.
- Easy to use, push over wire design.
- Polyethylene, split tube material, light weight and easy to handle.
- Male and female interlocking lengths for fast installation.

Scan for instructions



Part description:

Tiger Tails

Figure 1 DB35A	
Figure 2 DB45A	
Figure 3 LS70	
Figure 4 DB35ARB	
Figure 5 DB35ARB125	

### Dimensions Table (A)

Item No.	Length	Inner Diameter	Thickness	Weight
DB35A	8.2ft/2.5m	1.4"/35mm	0.11"/2.8mm	3.3lb/3.5kg
DB35ARB	8.2ft/2.5m	1.4"/35mm	0.11"/2.8mm	3.3lb/1.5kg
DB35ARB125	4.1ft/1.25m	1.4"/35mm	0.11"/2.8mm	1.65lb/0.75kg
LS70	6.6ft/2m	2.8"/70mm	-	3.3lb/1.5kg
DB45A	8.2ft/2.5m	1.8"/45mm	0.12"/3mm	4lb/1.8kg

Note: Any dimensions or weights figures are estimates only.

### Ratings Table (B)

1	<b>Testing on 120°C heated rod for 1 hour</b> <sup>(a)</sup>	No adverse functional effect on unit.	2	<b>Conforms to standard</b>	AS 4202 650V.
3	<b>Hardness rating</b>	105 Shore A.	4	<b>Accelerated UV testing</b>	All - 1000 hours LS70 - 2000 hours.

(a) Results obtained at Balmoral Engineering inhouse test lab for reference.

*Disclaimer: BALMORAL ENGINEERING, ROTAMARKA, TIGER TAILS and BIRDFLAPPA are trademarks owned by Balmoral Engineering Pty Ltd. The information in this document or product specification is believed to be correct as of the date of issue and is subject to change without notice. This document should be read in conjunction with the applicable Instructions For Use (IFU) document. Data within Balmoral Engineering Product Data Sheet (PDS) may be subject to tolerances. These tolerances will be defined within the applicable PDS or made available on request. Results and output data in this data sheet are indicative of lab testing protocols and may vary in field applications or environments. BALMORAL ENGINEERING makes no guarantees, expressed or implied as to the merchantability or fitness for purpose. The products are only to be used and installed by industry certified personnel. If applicable, maximum test speeds should be endured by the Products for a limited time period no greater than those described in the lab protocols. Imperial system units of measure are approximations only and have been converted from the data originally recorded in the metric system. Performance of the device in extreme weather events or harsh environments is not warranted. If BALMORAL ENGINEERING sells any component of a product or kit, we make no representations or guarantees as to the serviceability of the actual product or kit into which the component is being added. Furthermore, it is recommended that any such addition to the kit is done by BALMORAL ENGINEERING. In relation to the Balmoral Engineering Visual Warning series of products, it should be noted that not all visual responses to the device are going to be similar or alike. As such, no guarantees can be given as to the products effectiveness. Given the variety of factors that can affect the use and application of a product, some of which are within the user's knowledge and control, it is essential that the user evaluate the product to determine whether it is fit for a particular purpose and suitable for the user's method of use or application. The purpose of this document is to provide a description of the product and/or guidance to the installation thereof. When installing Balmoral Engineering products, due consideration must be given to the user's training and practice methodologies including any requirements of the entity who owns the infrastructure onto which the BALMORAL ENGINEERING Product is being installed. This must take precedence over any guidance BALMORAL ENGINEERING may provide. Notwithstanding, that all the above guidelines are followed, the ultimate responsibility for installing and maintaining the product correctly is with the end user. BALMORAL ENGINEERING accepts no liability for consequential damage relating to wildfires or bushfires particularly in regard to incorrect installation. As service environments may differ markedly with each application, the level of care required may change and is solely the responsibility of the end user. Any product images displayed are representative only. The above data sheet is provided as an estimate of performance and life and is not a guarantee or warranty. © 2026, All Rights Reserved, Balmoral Engineering Pty Ltd.*